



Rated voltage	AC 250 V 50Hz/60Hz
Rated current	16A (resistive load)
Contacts	SPST, auto-reset
Material of base	phenolic resin
Material of sensing cover	aluminum
Material of termina	nickel plated brass
Insulation Resistance	More than 10MΩ (with DC 500V megger)
Contact Resistance	≤50mΩ
Life(resistive load)	more than 60,000 cycles;
Approved	CQC/TUV
Marking series no.	KSD301 (Laser marking or tool impression)
Client's PN	

Customer should sign and stamp on this drawing before placing orders. If customer place orders without sign and stamp, we will consider customer has confirmed this drawing.

List of operating temperature

PN	Type	OFF (open)	ON (close)	Max. ambient temperature
CS180175-1	KSD301-9.5/16LE16S35	95±4°C	60±8°C	205°C
CS180175-2	KSD301-8.5/16LE16S20	85±4°C	65±7°C	205°C
CS180175-3	KSD301-6.0/16LE16X2	60±4°C	45±7°C	140°C

Undeclared tolerance: ±0.5mm Unit: mm Scale: 2 : 1 Size: A3	Title: Snap-Action Thermostat	Drawing no.: CS180175	REV.: A
		Type of product or spec. of material:	
Drawn by:			
Checked by:			
Date:	2018-5-19	FSTB TONGBAO-HUALONG CONTROLS CO., LTD.	