



Rated voltage and current (resistive load)	AC250V / 10 A	
Contacts	<input checked="" type="checkbox"/> SPST, auto-reset <input type="checkbox"/> SPST, manual reset <input type="checkbox"/> SPST, SOD (one shot; reset temp. <math>< 35^{\circ}\text{C}</math>) <input type="checkbox"/> DPST, manual reset <input type="checkbox"/> SPST, drop to ON temperature and power off to reset after cut out	
	Operating temperature	OFF: $20\pm 3^{\circ}\text{C}$ (open)      ON: $10\pm 5^{\circ}\text{C}$ (close)
	Material of base	<input checked="" type="checkbox"/> phenolic resin <input type="checkbox"/> ceramic <input checked="" type="checkbox"/> aluminum <input type="checkbox"/> brass <input type="checkbox"/> stainless steel
Material of sensing cover	<input checked="" type="checkbox"/> aluminum <input type="checkbox"/> brass <input type="checkbox"/> stainless steel <input type="checkbox"/> nickel plated brass <input type="checkbox"/> tin plated brass <input type="checkbox"/> brass <input type="checkbox"/> stainless steel	
Material of terminal	<input type="checkbox"/> nickel plated brass <input type="checkbox"/> tin plated brass <input type="checkbox"/> brass <input type="checkbox"/> stainless steel	
Insulation Resistance	More than 10M $\Omega$ (with DC 500V megger)	
Dielectric Strength	1500V 50Hz AC current, for one minute as bearing test. Resulted no breakdown, no flashover. <input checked="" type="checkbox"/> 100 $^{\circ}\text{C}$ <input type="checkbox"/> 140 $^{\circ}\text{C}$ <input type="checkbox"/> 185 $^{\circ}\text{C}$ <input type="checkbox"/> 205 $^{\circ}\text{C}$ <input type="checkbox"/> 220 $^{\circ}\text{C}$ <input type="checkbox"/> 245 $^{\circ}\text{C}$ <input type="checkbox"/> 280 $^{\circ}\text{C}$ <input type="checkbox"/> 320 $^{\circ}\text{C}$	
Max. ambient temperature	<input type="checkbox"/> 6,000 <input type="checkbox"/> 10,000 <input type="checkbox"/> 30,000 <input type="checkbox"/> 60,000 <input checked="" type="checkbox"/> 100,000	
Life cycles	<input checked="" type="checkbox"/> CQC <input type="checkbox"/> UL <input type="checkbox"/> CUL <input checked="" type="checkbox"/> TUV <input type="checkbox"/> VDE	
Approved	KSD301	
Marking series no.	KSD301	
Method of marking	Laser marking or tool impression	
Client's PN		

Customer should sign and stamp on this drawing before placing orders. If customer place orders without sign and stamp, we will consider customer has confirmed this drawing.

 Undeclared tolerance: $\pm 0.5\text{mm}$  Scale: 2 : 1 Unit: mm Size: A3	Title: Snap-Action Thermostat	Drawing no.: CS170141	REV.: A
Drawn by	Type of product: KSD301-2.0/10D16S10	ERP	ERP no.: *****
Checked by			
Date	2017-04-11		