



**NOTES:**

- 1、 POWER: 230V/2000W(+5%/-10%).
- 2、 HI-POT  $\geq 1500V/SEC$ , CUT OFF CURRENT: 1mA.
- 3、 INSULATION RESISTANCE:  $\geq 100M \Omega/DC500V$ , MIN
- 4、 PROCESS:AL RADIATING.
- 5、 LEAKAGE CURRENT TI BE 1.0mA MAX. WHILE ENERGIZED AT RATED VOLTAGE
- 6、 TUBE:SUS304.
- 7、 RESISTANCE WIRE MATERIAL:FE-CR WIRE.
- 8、 INSULATED FILLER:MAGNESIUM OXIDE POWDER
- 9、 LEAD-OUT ROD MATERIAL:#10 STEEL, PLATED.
- 10、 SEALING MATERIAL:SILICON RUBBER.
- 11、 DEVELOPED LENGTH:2690mm.

A (2:1)

ITEM	NAME	MATERIAL	RATING	QTY	CODE
5	BRACKET	SUS430	40*18*1.5	1	
4	Connector	SUS430	250#-M4-90°	2	
3	Connector	Ceramic	$\phi 7.8 \times 2.8 \times 5$	2	
2	COLN PIN	#10MILD STEEL	$\phi 2.5 \pm 0.1$	2	
1	SHEATH	SUS304	$\phi 8.0 \pm 0.05$	1	

MODEL:	DWG. NO:	CUSTOMER MODEL:	TITLE:
JL $\phi 8.0G3091$	20180619-6	260A	HEATING TUBULAR ELEMENT
	UNIT:	SCALE:	REV:
	mm	N. T. S	B
<b>FOSHAN TONGBAO HUAYU INDUSTRIAL., LTD.</b>			

		20180702

