



Rated voltage	AC250V 50Hz/60Hz	
Rated current	16A (resistive load)	
Contacts	SPST, auto-reset	
Operating temperature	OFF: (open) 55±3°C	ON: (close) 45±6°C
Material of base	ceramic	
Material of sensing cover	aluminum	
Material of termina	nickel plated brass	
Insulation Resistance	10MΩ以上 (DC 500V 兆欧表, 冷态) More than 10MΩ (with DC 500V megger)	
Contact Resistance	≤50mΩ	
Max. ambient temperature	140°C	
Life(resistive load)	more than 100,000 cycles;	
认证 Approved	TUV/UL	
Marking series no.	KSD301-G Laser marking or tool impression	
Client's PN		

Customer should sign and stamp on this drawing before placing orders. If customer place orders without sign and stamp, we will consider customer has confirmed this drawing.

 Undeclared tolerance: 0.5mm ±	Title:	Drawing no.:	REV.:
			A
Unit: mm	Scale: 2 : 1	Snap-Action Thermostat	ERP no.:
Size: A3			
Drawn by		Type of product or spec. of material:	
Checked by		KSD301-5.5/16LE16S10-G	
Date	2019-3-1	 FSTB TONGBAO-HUALONG CONTROLS CO., LTD.	