

Package	Part No. FYL-	Chip		Lens Appearance	Absolute Maximum Ratings				Electro-optical Data(At 20mA)			Viewing Angle 2 1/2 (deg)	Drawing No.
		Material/Emitted Color	Peak Wave Length p (nm)		(nm)	Pd (mw)	If (mA)	Peak (mA)	Vf(V)		Iv (mcd)		
									Typ	Max	Typ		
T-1 3/4 Standard 1.0" Lead 5	5013SRD	GaAlAs/SH Super Red	660	Red diffused	20	60	30	150	1.85	2.20	80	60	L-011
	5013LRD	GaAlAs/DH Super Red	660	Red diffused	20	60	30	150	1.85	2.20	120	60	
	5013SRT	GaAlAs/SH Super Red	660	Red trans	20	60	30	150	1.85	2.20	250	20	
	5013SRC	GaAlAs/SH Super Red	660	Water clear	20	60	30	150	1.85	2.20	250	20	
	5013LRC	GaAlAs/DH Super Red	660	Water clear	20	60	30	150	1.85	2.20	600	20	
	5013URC	GaAlAs/DDH Super Red	660	Water clear	20	60	30	150	1.85	2.20	1000	20	
	5013UEC	AlGaInP/Ultra Orange	630	Water clear	17	65	30	150	2.10	2.50	2000	20	
	5013UYC	AlGaInP/Ultra Yellow	590	Water clear	15	65	30	150	2.10	2.50	2200	20	
	5013UGC	AlGaInP/Ultra Green	574	Water clear	30	75	30	150	2.20	2.50	700	20	
	5013PGC	InGaN/SiC Ultra Green	525	Water clear	36	110	30	150	3.80	4.50	3000	20	
	5013BGC	InGaN/SiC Ultra Green	505	Water clear	30	110	30	100	3.80	4.50	3000	20	
	5013UBC	InGaN/SiC Ultra Blue	470	Water clear	30	120	30	100	3.80	4.50	1500	20	
	5013BC	InGaN/SiC Super Blue	470	Water clear	30	120	30	100	3.80	4.50	1000	20	
	5013VC	InGaN/SiC UV	405	Water clear		120	30	100	3.80	4.50	200	20	
	5013UWC	InGaN/SiC Ultra White		Water clear		120	30	100	3.80	4.50	6000	20	
	5013WC	In GaN/SiC Super White		Water clear		120	30	100	3.80	4.50	2500	20	

L-011

FYL-5013xx Series

