


The H position shown in Fig

Technical Parameters								
Parameter of temperature	WARM (H/off)			LOW(L/off)				
	ON(τ)	---	---	---	---			
	OFF(τ)	120±6	(0)	---	---			
	DIFF(τ)	5.5±3.5	---	---	---			
Test conditions of parameters:(1)the parameters will be based on the value of the 2nd test; (2)ambient temperature:25°C								
Electric parameters	Rated voltage V		AC					
	Rated current A		250		400			
	Current of no induced load		P-1	15	P-1	15		
			P-2	3	P-2	3		
Wiring form	S.P.D.T		 temperature rising OFF					
Grounding resistor	<50mΩ							
Insulation resistor	>100MΩ							
Insulation and voltage resistance	2500V/1s							
Filling form	liquid							
life	100,000 Cycles							
Rate of temperature raising and dropping	1°C/min (medium for measuring temperature:liquid)							
Permitted temperature	side of body: 120°C side of temperature induced: 150°C							
Form of installation	No limit							
Torque of operation	The torque strength from zero position to on position max:4Ncm; Turning torque from on position to High position:<2Ncm							

REMARKS:

The operating condition is 25°C ambient temperature, if ambient temperature change the operating temperature parameter should be modified.

THERMOSTAT

WY120Z-E