



NOTE:  
 1. 3-4 Main switchcloses on temperature rise  
 2. 3-6 Signal switch : closes at temperature rise  
 3. C:Compressor  
 4. L:Signal Lamp

(A) TONGBAD CODE CHANGED

|  |                |                                 |        |         |
|--|----------------|---------------------------------|--------|---------|
| Operating Temperature (737mmHg)                        | SIGNAL INK(°C) | Warm                            | Normal | Cold    |
|  | CUT INK(°C)    |                                 |        |         |
| Operating Temperature (760mmHg)                        | CUT OUT(°C)    |                                 |        |         |
|  | DIFF(°C)       |                                 |        |         |
| The second testing temp is taken as an accurate value. |                |                                 |        |         |
| Operating Temperature (760mmHg)                        | SIGNAL INK(°C) | Warm<br>above CUT in<br>-11±2.0 | Normal | Cold    |
|  | CUT INK(°C)    | -15±1.5                         |        |         |
|  | CUT OUT(°C)    | -22±1.5                         |        |         |
|  | DIFF(°C)       |                                 |        | -33±2.5 |
| The second testing temp is taken as an accurate value. |                |                                 |        |         |

|  |                                    |                                      |         |
|--|------------------------------------|--------------------------------------|---------|
| Electrical Ratings                         | Rated Amperes (A)                  | 250                                  | AC      |
|  | Non-Inductive Current              | 3-4/3-6                              | 120     |
| Insulation Resistance                      | Inductive Load                     | 0.5--6                               | 3-4/3-6 |
|  | Locked Rotor                       | 0.5--36                              | 1--10   |
| Dielectric Strength                        | Rated Volts (V)                    | 0.45                                 | 1--40   |
|  | Kind of charge                     | More than 100MΩ with a DC500V megger |         |
| Conditions of Operating Temp.              | TS>TB                              | AC 150V for one minute               |         |
|  | TS<TB                              | Gas(R290)                            |         |
| Response Characteristic of Sensing Element | Temp. change rate: ≤ 1°C/min       |                                      |         |
|  | Max. Temperature                   | Around the Main Frame: 70°C          |         |
| Life of Contact                            | Rotating Moment of Adjusting shaft | Around the Sensing Element : 80°C    |         |
|  |                                    | 200,000 Cycles                       |         |

Remarks :  
 1. The length of capillary immersed in the testing medium shall reach more than 150 mm.  
 2. The temperature characteristic is under a 760mmHg of atmosphere at 25°C  
 3. Thermostat shown in COLD position  
 4. The material requests according to the ROHS.

|              |                 |      |           |                     |  |
|--------------|-----------------|------|-----------|---------------------|--|
| Edition      | Religger Number | SIGN | DATE      | Pressure Thermostat | Customer: VETRA                            |
| DESIGNED BY  | S. B. Chan      |      | 20.1.19   |                     |  |
| CHECKED BY   | M. G. Tan       |      | 2020.1.19 |                     |  |
| INSPECTED BY | G. H. Chen      |      | 2020.1.19 |                     |  |
| APPROVED BY  | L. H. Lin       |      | 2020.1.19 | WIRING DIAGRAM      | FOSHAN TONGBAD HUATONG CONTROLLER CO.,LTD. |