

SPECIFICATIO					
	DGKD/JS-PB-002		B / 2		
ITEM		TEST CONDITIONS		PERFORMANCE	
6.5	HEAT TEST	THE SWITCH SHALL BE STORED AT A TEMPERATURE OF 70±2℃ FOR 48 HOURS. THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.		THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART.	
6.6	HUMIDITY TEST	THE JACK SHALL BE STORED AT A TEMPERATURE OF 40±2℃ AND A HUMIDITY OF 90% TO 95% FOR 96 HOURS. THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITION FOR 1 HOUR PROCEDURES BE MADE.		THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART.	
7.0	CONSERVATION TEMPERATURE	<p>THE SWITCHES' STORE CONDITIONS REQUIREMENT AND STORE TIME LIMIT:</p> <p>1. THE SWITCHES PACKED IN THE CARTON BOARD BOXES AND WOODEN BOXES CAN BE TRANSPORTED BY ANY KINDS OF VEHICLES, BUT NEED AVOIDING BEING STRICKEN BY RAIN, SNOW AND MECHANISM.</p> <p>2. THE SWITCHES SHOULD BE KEPT UNDER THE BELOW CONDITIONS: THE TEMPERATURE IS KEPT WITHIN THE LIMITS OF SUBZERO THEN DEGREE CENTIGRADE TO FORTY DEGREE CENTIGRADE; THE RELATIVE HUMIDITY SHOULD BE NOT MORE THAN EIGHTY PERCENT AND THERE IS NO ACID, ALKALI, SULFIDE, OZONE, ALKALINE AIR AND ANY OTHER POISONOUS GAS AROUND THE STOREHOUSE.</p>			
8.0	CHINA OF ORIGIN	MADE IN CHINA.			
9.0	ROHS COMPLIANT	<p>ON THE RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT, THE USE OF PROHIBITED SUBSTANCE IS LIMITED TO:</p> <p>1. Cd <100ppm;</p> <p>2. Pb, Hg, Cr (VI), PBB AND PBDE <1000ppm.</p> <p>3. INCLUDE THE RANGE OF THAT RoHS RELEASE.</p>		MEET THE ABOVE REQUIREMENT.	