



NOTES:

1. Rating: AC250V 16A、AC125V 16A
2. Hi-potest: 2500V 0.5mA 1S
3. Open on rising Temp. at High: $__^\circ\text{C}\pm 5\text{K}$
4. Operation angle: $180\pm 5^\circ$
5. On angle: $90\pm 20^\circ$ (R. T. 25°C)
6. Approval: CQC、TUV、UL

图号 Drawing No.	高端断开温度 Open on rising Temp. at High	标识(G) Marking
KST501-N-16B44/60	$60^\circ\text{C}\pm 5\text{K}$	60
KST501-N-16B44/70	$70^\circ\text{C}\pm 5\text{K}$	70
KST501-N-16B44/90	$90^\circ\text{C}\pm 5\text{K}$	90

未注公差: $\pm 0.12\text{mm}$ Undeclared tolerance: $\pm 0.12\text{mm}$		标题 Title: 闪动式温控器 Thermostat		图号 Drawing no.: ERP编号 ERP no.:	版本 Rev.: A
单位 Unit: mm 幅面 Size: A4 共1页 第1页	比例 Scale:	产品型号或材料规格 Type of product or spec. of material: KST501-N 系列 KST501-N series			
出图 Drawn by: 审核 Checked by: 日期 Date:	佛山市通宝华龙控制器有限公司 TONGBAO-HUALONG CONTROLS CO., LTD.				